

## S3010 Standard High Torque BB Servo



S3010 Standard High Torque BB Servo

Rating: Not Rated Yet

### Price

Price with discount \$22.30

Salesprice with discount

Sales price \$22.30

Sales price without tax \$22.30

Discount

Tax amount

[Ask a question about this product](#)

### Description

This is the Futaba Standard Size Ball Bearing High Torque Servo. This servo can produce high-current draw from your batteries. If using NiMH or LiPo batteries, make sure they are capable of delivering approximately 2A for each servo.

**FEATURES:** Ideal for high-torque applications requiring a standard size servo Universal connector fits Futaba, Hitec, JR, KO Propo, Airtronics Z, and Tower Hobbies. Does not fit old Airtronics A plug w/out adapter Nylon gears One bearing pre-mounted on output shaft. One year warranty

**INCLUDES:** One Futaba standard size high torque servo with; One 1.4" (35mm) diameter round servo wheel One 1.5" (39mm) diameter 4 point servo wheel One 1.25" (32mm) diameter 6 point servo wheel Four 2mm x 11mm phillips screws Four rubber grommets & Four metal eyelets

**REQUIRES:** Small phillips screwdriver to mount to surface

## **Futaba Products: S3010 Standard High Torque BB Servo**

---

**SPECS:** Speed: 0.20 sec/60° @ 4.8V 0.16 sec/60° @ 6.0V Torque: 72 oz-in (5.2 kg-cm) @ 4.8V and 90 oz-in (6.5 kg-cm) @ 6V Dimensions: 1.6 x 0.8 x 1.5" (1-9/16 x 13/16 x 1-1/2") (40 x 20 x 38mm) Weight: 1.5oz (1-7/16oz) (41g) updt

**BOX DIMENSIONS: 2.63" W. X 1.50" H. X 3.38" L. BOX WEIGHT: .18 LBS.**