3PRKA 2.4G FHSS w/R203GF





3PRKA 2.4G FHSS w/R203GF

Rating: Not Rated Yet **Price**

Price with discount \$79.89

Salesprice with discount

Sales price \$79.89

Sales price without tax \$79.89

Discount \$-14.10

Tax amount

Ask a question about this product

Description

This is the 3-Channel Futaba 3PRKA 2.4GHz FHSS Radio System with the R203GF Receiver.

FEATURES: Ideal upgrade for radios found in RTR vehicles Throttle and steering trim and reverse Steering dual rate dial Throttle end point adjustment Channel three switch Throttle fail safe One year limited warranty through Hobby Services beginning at date of purchase

INCLUDES: Futaba 3PRKA 2.4GHz FHSS Transmitter, R203GF Receiver, Instruction Manual and On/Off Switch

REQUIRES: Servos of modeler's choice Four AA batteries for transmitter

SPECS: Transmitter: Transmitting Frequency: 2.4GHz band Power Requirement: Four AA cells Current Drain: 100mA or less Receiver; Dimensions: 1.54 x 1.02 x 0.39" (39 x 26 x 10mm) Weight: 0.28oz (8g) Operating Voltage: 4.8 - 7.4V (shared with servo) Battery Fail Safe Voltage: 3.8V* Current Drain: 30mA at no signal *Battery fail safe voltage is set for 4-cell NiCd/NiMH battery Battery F/S does not work properly when other type of battery is used

COMMENTS: 2.4GHz FHSS is not compatible with FASST systems. Normal mode frame rate is (FHSS/S-FHSS) 13.63ms and accepts any type of servos or peripherals. High-Speed mode (in 4PL tx only), with an output of 6.8ms accepts digital servos including the BLS series and most peripheral equipment such as brushless ESCs updakzh

BOX DIMENSIONS: 8.00" W. X 4.63" H. X 12.13" L. BOX WEIGHT: 1.25 LBS.