

HS-5125MG Servo Super Thin Universal



HS_5125MG_Servo__50bfabc9129f5.jpg



HS-5125MG Servo Super Thin Universal

Rating: Not Rated Yet

Price

Price with discount \$48.49

Salesprice with discount

Sales price \$48.49

Sales price without tax \$48.49

Discount

Tax amount

[Ask a question about this product](#)

Description

This the Hitec Super Thin Digital Wing servo with a Universal Futaba J, Hitec S, JR and Airtronics Z Connector. These servos are used in confined spaces where a thin or low profile servo might be required.

FEATURES: Digital and MOSFET Amp

Indirect Drive Potentiometer for longer life

Dual ball bearing

Gold plate connector

Narrow dead band width and high standing torque

Strong four metal gears and one plastic gear

One metal servo horn

Plastic hardware servo horns and screws

Hitec "S" connector

Instruction sheet

Hitec Servos Only: HS-5125MG Servo Super Thin Universal

INCLUDES: One digital servo
Hardware

REQUIRES: Hitec receivers

SPECS: Length: 1.18"(30mm)
Width: 1.33"(34mm)
Height: .39" (10mm)
Weight: 24g (.84oz)
Output speed: .17 sec 60 degrees at 4.8V
Output torque: 41.66 oz-in (3 kg-cm) at 4.8V
Pulse data: 3-5V peak to peak square wave pulse. Pulse duration
is from 0.9mS to 2.1mS with 1.5mS as center.
Pulse refreshes at 50Hz (20mS)
Voltage range: 4.8-6V
Wire color: Black is Ground, Red is center, Power, third wire is
Signal
Direction rotation: Hitec servos turn in a clockwise direction

COMMENTS: Servo will work in gliders or wings, or any thin aircraft wing.