

HS-5645-MG SERVO



HS_5645_MG_SERVO_4cb92ce5c4a7d.jpg



HS-5645-MG SERVO

Rating: Not Rated Yet
Price

Price with discount \$55.00

Salesprice with discount

Sales price \$55.00

Sales price without tax \$55.00

Discount

Tax amount

[Ask a question about this product](#)

Description

This is a Hitec Super Torque, Metal Gear, that will work with Futaba J, Hitec S, JR, and Airtronics-Z radio systems.

FEATURES: EPA, Speed, Direction, and Fail-Safe Programmable (see COMMENTS). MOSFET amplifier. Gold plated contacts. Three metal gears Dual ball bearings. Indirect drive long life potentiometer. High standing torque. Watertight and dustproof. Includes blue aluminum, heat-treated servo arm (see COMMENTS). Works with fixed wing aircraft and helicopters up to 40 pounds, 1/10th and 1/8th on- or off-road vehicles.

INCLUDES: One digital high torque servo with 12" wire and S/JR/Air-Z connector One white small X-shaped servo horn. One red Large X-shaped servo horn. One white adjustable servo horn. One white offset straight servo horn. One white disc servo horn. One blue anodized, heat treated servo arm horn. Four 2 x 14mm mounting screws Four brass eyelets Four black rubber vibration isolators.

REQUIRES: Futaba J Hitec, JR, or Airtronics-Z radio system

SPECS: Speed: 0.23 sec/60° at 4.8V Speed: 0.18 sec/60° at 6.0V Torque: 143.03 oz-in at 4.8V Torque: 164.2 oz-in at 6V Length: 1.59" (40.6mm) Width: 0.77" (19.8mm) Height: 1.48" (37.8mm) Weight: 2.11oz (60g)